

2/PR 15

09/700172

526 R PCT/PTO 13 NOV 2000

Translation of PCT International
Application No. PCT/EP00/01599
Attorney Docket No. 951/49129

A

FUEL SYSTEM FOR A MOTOR VEHICLE
Background And Summary of The Invention

The present invention relates to a fuel system for a motor vehicle ~~according to the introductory clause of Claim 1.~~

Inv
AI

Fuel systems for motor vehicles are already known in which
5 a fuel filter is provided, where the fuel filter can be installed
inside and/or outside a fuel container. The fuel flow through
these filters is only ever in one direction. Because of this, the
dirt contained in the fuel is increasingly deposited over time on
the inflow side of the filter. If there is a large amount of dirt
10 in the fuel, a filter cake can form which leads to an increase in
throughflow resistance. This means that the demands on the
performance of the fuel pump within the fuel system also
increase.

This aim of the present invention is to create a fuel system
15 for a motor vehicle in which the throughflow resistance does not
increase over the lifetime of the vehicle or increases only
relatively slightly.

This aim is fulfilled by the features described in the
~~characterizing section of claim 1.~~

Inv
R2
R0

~~The fuel system according to the invention exhibits a fuel~~
filter in which a deposition tank is provided. In addition a
pressure accumulator is built into the system in such a way that
the fuel which is in the pressure accumulator is depressurized
after the engine has been switched off and rinses the filter from
25 the fuel outlet side or clean side toward the fuel inlet side or
dirt side. By these means the advantage is created that dirt
which has collected on the fuel inlet side is released from the

filter and collects in the deposition tank.

The deposition tank of the present invention is advantageously formed by means of the structure of the housing, for example by the provision of guide vanes, in such a way that fuel does not flow through the deposition tank and therefore the deposited dirt is not disturbed.

The fuel filter according to the invention can advantageously be located on either the pressure side or the suction side within the fuel system, in other words, behind or in front of the fuel pump.

In an advantageous embodiment, with the fuel filter located on the pressure side a pressure accumulator is installed in the direction of the engine after an outlet opening of the filter housing, and with the fuel filter located on the suction side after an outlet opening of the fuel pump, and in both cases is installed in front of a pressure regulator with an upstream non-return valve. The positioning of a non-return valve between a branch point leading to the pressure accumulator and the pressure regulator prevents the fuel pipeline to the motor from emptying.

In an advantageous embodiment a delay valve is provided in the fuel system in order that filling of the pressure accumulator does not influence the buildup of pressure in the fuel system after the engine has been started.

The fuel system which is the subject of the present invention is particularly advantageous in that the fuel filter achieves a longer lifetime. A further advantage is that by means of the structure of the fuel filter as embodied in the invention,

the filter volume can be decreased in comparison with a known fuel filter while maintaining the same lifetime.

Because the fuel filter is cleaned each time the engine is switched off, the volume throughflow resistance of the fuel filter remains approximately constant. Therefore, the fuel pump of the fuel system only needs to exert normal pressure and not increased pressure as is the case with a blocked fuel filter, so that the lifetime of the fuel pump is higher in comparison with fuel systems with traditional fuel filters.

A further advantage is that the fuel filter, the pressure regulator, the fuel pump, the non-return valve, the pressure accumulator and possibly the surge chamber can be implemented in the form of a preassembled unit, and therefore the emissions are also less.

Several embodiments of the invention are described as examples in the following text with reference to the drawing, whereby

Figure 1 shows a basic diagram of a fuel system, where the fuel filter is located on the pressure side; and

Figure 2 shows a basic diagram of a fuel system, where the fuel filter is provided on the suction side.

Detailed Description of Drawings

Figure 1 shows a first embodiment of a fuel system 1 where a fuel pump 2 transports fuel 4 from a fuel container 3 for example via a surge chamber which is not shown by means of fuel pipelines 5 to a fuel filter 6. The fuel filter 6 exhibits a housing 7 in which a filter material 8, for example woven filter

material or filter paper, is located.

5 Beneath the filter material 8 a deposition tank 9 is formed
into housing 7 which is arranged or protected so that fuel 4
flowing through filter material 8 does not influence dirt 10
collecting in deposition tank 9. For example, guide vanes or
walls²² can be provided in housing 7 which prevent swirling up of
the dirt 10 in deposition tank 9 due to the fuel flow.

in Fig. 1,

A In the embodiment shown⁴⁵ fuel filter 6 exhibits at least one
inlet opening 11 on housing 7 for the fuel 4 to be cleaned and at
10 least one outlet opening 12 from which the cleaned fuel 4 flows
into pipeline 13. The filter material 8 next to the inlet opening
11 becomes dirty most quickly and for this reason this side of
filter material 8 is referred to⁴⁵ the dirt side ~~in the following~~
A ~~text~~ A pipeline 14 leading to a pressure accumulator 15 is
15 connected to pipeline 13 at a branch point 20. The cleaned fuel
4 flows via a non-return valve 16 and a pressure regulator 17
connected to it through pipeline 21 to engine 18.

20A When the engine 18 is running, the fuel pump 2 transports a
predetermined volume of fuel 4 into pressure accumulator 15,
which can, for example, be in the form of a membrane pressure
accumulator. After the engine 18 is switched off, the pressure
accumulator 15 is depressurized so that the fuel 4 which is
located in pressure accumulator 15 flows back via pipeline 13 and
through outlet opening 12 into fuel filter 6 and there rinses the
25 filter material 8 so that the dirt 10 which has particularly
collected on the dirt side of filter material 8 is released and
arrives in deposition tank 9 via appropriate means. The fuel 4
which rinses the filter material then flows back through inlet
opening 11, pipelines 5, through fuel pump 2 to the inlet point

19 in fuel container 3. Because of the location of non-return valve 16 between branch point 20 to pressure accumulator 15 and pressure regulator 17, pipeline 21 to engine 18 is not emptied during rinsing of fuel filter 6.

5 The second embodiment of fuel system 2 shown in Figure 2 differs from the first embodiment of the fuel system 1 shown in Figure 1 in that fuel filter 6 is positioned on the suction side
A ~~of the fuel pump 2.~~ A further difference between the two figures is in the flow direction of fuel 4 which is shown. While in
10 Figure 1 fuel system 1 is shown with engine 18 running, as indicated by the flow direction of fuel 4 shown by arrows, Figure 2 shows fuel system 1 after engine 18 has been switched off, where the fuel 4 located in pressure accumulator 15 flows back through fuel pump 2 and fuel filter 6 into fuel container 3, as
15 is also indicated by arrows.

Fuel pump 2 accordingly pumps fuel 4 out of fuel container 3 through fuel filter 6 and transports this fuel 4 via a non-return valve 16 and a pressure regulator 17 to engine 18. In addition, when engine 18 and fuel pump 2 are in operation, a
20 predetermined volume of fuel 4 is transported to pressure accumulator 15.

In both embodiments a delay valve can be provided in branch pipeline 14, so that pressure accumulator 15 is filled with fuel 4 with a time delay after starting of engine 18.